

RSD AudioBox II HLX-2200 Server



Description

Richmond Sound Design AudioBox II Model HLX-2200 - 2x PCI Standard w/ PCI-Express Option

Features

- Certified by Richmond Sound Design to be Compatible with their SoundMan-Server Software
- 2RU Rack Mount Server Chassis w/ Locking Front
- 300W ATX 80+ Certified Active PFC Power Supply
- Intel LGA-775 G41 micro-ATX Mainboard - 4x SATA, 2x PCI, 1x PCI-Ex16, 1x PCI-Ex1
- Intel Pentium E5700 3.0GHz Socket 775 65W Dual Core CPU
- 4GB DDR3-1066 PC3-8500 Memory
- 250GB SATA 7200 RPM Hard Drive - Internal Mount
- Internal USB Dongle Support Cable
- DVD/CD R/W Optical Drive
- Stock Intel CPU Cooler
- 2x80mm High MTBF Case Fans
- External Rear I/O - 4x USB 2.0, 1x D-Sub, 2x PS/2, 1x Com, 1x LPT, 1x LAN, 3x Audio
- MS Win7 Home Premium 32-Bit O/S
- Single SSD Upgrade:** 80GB SSD

Terms and Conditions: Price includes system integration, testing, standard shipping for procurement of custom hardware and six month technical support warranty. Price does not include shipment to customer. All shipping FOB. Hardware covered under their individual manufacturer warranties. Software support provided by their respective owners. Return/refund of items subject to supplier terms. Build labor non-refundable for completed systems. Customer responsible for insurance covering their property while on Hive Logix premises. Adjustments to quote may be required at time of purchase due to frequent fluctuation in hardware pricing. Minor variations to hardware specs may be necessary due to part availability. Allow 5-7 business days turn-around time. Price does not include audio signal processing cards. Please contact [Richmond Sound Design](#) for additional hardware specifications.